



*a traditionally styled ornamental bollard designed to resemble its cast iron relative. The body of the bollard is manufactured from mild steel which is galvanised as standard to ensure its longevity. Caps and rings manufactured from cast iron are welded on to the steel body to complete the design.*

*The bollards are available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information*

## Product Range

Order Code	Description	Lift out weight	Weight
138 120 137	Removable (Galvanised)	14.3kg	19.0kg
138 120 140	Removable (Galvanised and Black)	14.3kg	19.0kg
138 120 142	Removable (Galvanised and Colour)	14.3kg	19.0kg

## Installation Parts

138 100 906	40mm Brass Padlock with 2 keys (Random Key)
138 100 907	40mm Brass Padlock with 2 keys (Identical Key)
138 150 206	Additional Socket

## Product details

1000mm above ground  
267mm below ground  
114mm diameter tube  
3mm wall thickness

## Installation & use

Removable bollards require an excavated hole of at least 300mm square and 400mm deep for the socket. recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).